

77202

Turn-n-Wrap high profile foot switch operated turntable with manual operated quick load film dispenser

OVERVIEW

If you're tired of holding stretch film by hand upgrade to the 77202 that uses machine grade stretch film. This model has a fixed speed turntable and a manual hand crank film dispenser to make your stretch wrapping jobs easier. Just load the 48" round or octagon turntable, attach the film, press the footswitch and manually move the Quick-Load dispenser up and down as the load is rotated. Get tighter load security, higher productivity and minimize worker fatigue it couldn't be simpler.



SPECIFICATIONS

Maximum Load Size:	52" x 52" x 74"
Production Capacity:	40 loads per hour
Machine Dimensions:	85"L x 48"W x 83"H
Weight Capacity:	4,000 LB.
Electrical Data:	120 VAC 60 Hertz 20 Amps. Conventional style 3 prong power cord. UL approved components.
Turntable Size:	48" round steel diamond deck or 48" octagon steel diamond deck w/5" skirt.
Turntable Height:	14 5/8"
Turntable Drive:	3/4 hp DC motor (totally enclosed fan cooled). Variable speed turntable 0-15 RPM with soft start and soft stop. Lubrication free enclosed gear drive design. Synthetic lube in all gearboxes (-30 to 120 °F).
Controls	Shielded Footswitch Start / Stop

Film Delivery	Quick Load Film Dispenser (Load Brake) Manual Hand Crank Dispenser Stretch Level 30% - 225% Force to Load Accepts 12" – 20" Rolls of Film on standard 3" Core
Film Carriage	74" Wrap Height (Optional Wrap Height Available) Variable Speed Carriage 0-20 FPM 1/4 HP 90 Volt DC Motor 12 Point UHMW Carriage Guidance Supports
Frame Construction	Custom Formed Steel Channel All Welded Steel Construction
Warranty	3 Year Limited Warranty (100% of all Components)
Shipping Weight	925 lbs.