

Additional Information

1. All pinch points are shielded and marked.
2. Entire turntable is skirted so trash or clothing cannot come into contact with drive components.
3. Control panel is easy to read and has large E-stop push button to kill the machine in case of emergency or potential injury.
4. All electrical wiring is enclosed in conduit to prevent cutting or damaging wires.
5. All machines come with complete operation manuals component diagrams and wiring schematics for easy trouble shooting.
6. All machines are forklift portable from front and rear. It is impossible to damage internal components (i.e. chain) no matter the extent of fork penetration. This also prevents forklift operators from lifting the base under the tower or other inappropriate places.
7. Variable speed turntable with soft start and soft stop that can be adjusted for light loads or heavier loads.
8. All components are UL listed and UL approved.
9. All components are non proprietary and can be purchased @ Grainger, Mc Master Carr, ETC....
10. All standard machines are shipped fully assembled and only requires the customer to unpack the machine and place next to 110 power.
11. Standard models can be placed in refrigerate or environment that are 20 degrees above 0.
12. Top and bottom limit switches that stop the dispenser if it misses the top of load.
13. 4 point Easy access turntable lubrication cam followers that can be lubricated with out disengaging drive or removing turntable top that allows one person maintain.
14. No threading film carriage which eliminates pinch points this is due to only one powered roller.
15. Each models is shipped with full wiring schematics and operational manuals.